




Female Branch Tee



METRIC OD Tubes x Female NPT Threads

T Tube OD	P NPT Female	Fluid Fit Part No.	A	Ax	B	C	D	E min.	F A/F	G A/F	H	Hx	Hy
3	1/8	FBTM 3-2N	49.2	24.6	10.4	15.3	12.9	2.4	14	11	36.0	18.0	19.0
6	1/8	FBTM 6-2N	54.0	27.0	10.4	17.7	15.3	4.8	14	14	39.2	19.6	19.0
6	1/4	FBTM 6-4N	59.6	29.8	15.0	17.7	15.3	4.8	19	14	44.8	22.4	22.4
8	1/8	FBTM 8-2N	59.8	29.9	10.4	18.6	16.2	6.3	16	16	44.8	22.4	19.0
8	1/4	FBTM 8-4N	61.2	30.6	15.0	18.6	16.2	6.3	19	16	46.2	23.1	22.4
10	1/4	FBTM 10-4N	67.0	33.5	15.0	19.5	17.2	7.9	19	19	51.8	25.9	22.4
12	3/8	FBTM 12-6N	72.0	36.0	15.0	22.0	22.8	9.5	22	22	51.8	25.9	22.4
12	1/2	FBTM 12-8N	77.6	38.8	19.8	22.0	22.8	9.5	27	22	57.4	28.7	28.5
16	1/2	FBTM 16-8N	79.0	39.5	19.8	22.0	24.4	12.7	27	25	59.4	29.7	28.5
25	1	FBTM 25-16N	107.2	53.6	25.4	26.5	31.3	22.3	41	38	82.8	41.4	38.1

Fluid Fit Engineers

Unit 11, Pereira Compound, Near Vaishali Nager, S. V. Road

Mumbai-400 102, Maharashtra (India)